



- NOTES:**
1. FINISH: HOT DIP GALVANIZED PER ASTM A123
  2. MATERIAL: STEEL PLATE PER ASTM A572 GR.50, DYWIDAG THREADBAR SET PER ASTM A615 GR. 75, 107KSI MIN YIELD STRENGTH FOR TIEBACK ADAPTER
  3. ULTIMATE ASSEMBLY STRENGTH: 111,000 LBS
  4. ALL WELDING TO BE DONE BY WELDERS CERTIFIED UNDER SECTION 5 OF THE AWS CODE D1.1

<p><b>HELIICAL ANCHORS INC.</b></p> <p><small>THIS DRAWING CONTAINS CONFIDENTIAL INFORMATION OF HELIICAL ANCHORS INC. THIS DOCUMENT MAY NOT BE REPRODUCED IN ANY FORM WITHOUT THE EXPRESS WRITTEN PERMISSION OF HELIICAL ANCHORS INC.</small></p>		<p><b>2-7/8 Helical Anchor Tieback Assembly</b></p>	
DRAWN BY:	DKM	SIZE	PART/CAT/NO./SKU NO.
DATE:	01/24/11	A	TBA278
DWG NO.	HA-00362	SCALE:	NOT TO SCALE
		REV	
		SHEET	1/1